

# Product Data Sheet



## ASMACO ANTI GRAVEL AEROSOL

### Product Description:

ASMACO Anti gravel aerosol is specially developed on the base of high polymer rubber and synthetic resin for the protection of automobiles and car body surface from gravel, rust, salt, and stones. It can be used for threshold, spoilers, wheel arches, front and rear aprons, door bottoms and other parts. Compatible with all kinds of paints and lacquer. It reduces the noise which is created between the road and wheel.

### Key Performance Properties:

- Does not contain bitumen and asphalt
- Reliable protection from pebbles, abrasive impact of dirt, sand, petrol, oils, water, and salts.
- Resistant to temperature changes.
- Reduces noise inside a car.
- Highly adhesive.
- High spreading capacity.
- Compatible with all kinds of paints and lacquers.
- Makes car bodies last much longer.
- Spreading capacity (depending on coat thickness) is 2.5–3 M<sup>2</sup>.
- Full drying time is 2 hours at t +20°C.

### Applications:

- Protects the lower flanks of the car body against stones and corrosion.
- The film also largely absorbs noise and vibration.
- Anti-gravel below the bumpers and side panels of cars.
- Anti-resonance product in wheel arches and undersides of cars.

### Direction For Use:

- Make sure that the underside of the car is completely dry, clean and free of grease. Cover the parts that do not need a treatment.
- Shake the can for at least 3–5 min — it will make a coat homogeneous and prevent the injector from being blocked.
- Shake the can from time to time when using.
- Spray to test.
- Hold the can upright. Apply a thin coat at 25–30 cm distance. For the best effect make 2–3 thin coats with 5 min intervals.
- To clear after use, turn can pointing nozzle up and away from user and activate for 1 or 2 seconds.

### Restriction:

- Do not use this product if rain is imminent.
- Do not expose to temperatures exceeding 50°C
- Do not spray on naked flame or any incandescent materials.
- Keep out of reach of children.
- Do not pierce or burn even after use.
- It may burn above 50°C



## ASMACO ANTI GRAVEL AEROSOL

# Product Data Sheet



## Typical Properties:

Appearance	Paint in aerosol can
Color	Matt Black
Odor	Solvent
Solid %age	45±5
Density	1.05±0.05 g/cm <sup>3</sup> @20°C
Drying Time Soft dry	10±5 minutes
Drying Time (Hard dry)	< 30 minutes
Complete curing	24 hours
Flash Point	< 0°C (Closed Cup)
Inside pressure (m.pa) @ 25 °C	0.5 ± 0.10

## Storage and Shelf Life:

The shelf life of ASMACO Anti gravel aerosol is 2 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children. Store in cool, dry conditions, between +5°C and 25°C.

## Packaging:

ASMACO ANTI GRAVEL AEROSOL 500 ML - 12 CANS/CTN

## Shipping Limitations: None

### Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

**Non – Warranty:** Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م  
**ANCHOR ALLIED FACTORY L.L.C.**

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107  
P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS  
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE  
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE