



مصنع انكور الايد ذ.م.م.

ANCHOR ALLIED FACTORY L.L.C.

MFG. OF SILICONE, ACRYLIC & POLYURETHANE SEALANTS, WATERPROOFING COATINGS, AEROSOL PRODUCTS AND ADHESIVE TAPES
P.O. Box: 21152, Sharjah, U.A.E. Tel.: +971-6-5342091, Fax: +971-6-5342107
E-mail: info@anchorallied.com Website: www.anchorallied.com



TECHNICAL DATA SHEET

TUB & TILE CERAMIC SPRAY PAINT

1. DESCRIPTION:

Tub & Tile CERAMIC aerosol is a one-step acrylic spray paint designed to provide excellent adhesion, durability and color retention in high moisture areas. This smooth, glossy, waterproof finish is suitable for use on tiles, sinks and tubs.

2. PROPERTIES:

- Restoration and coating of bath tubs, washbasins, kitchen sinks.
- Quick drying, smooth finish
- Premium quality, high durable.
- Ideal for wood, metals, plastic, automotive and motorcycle, equipment's etc.
- Heat Resistance up to 100°C
- Interior and exterior application.
- Non fading, none yellowing, weather resistant.
- High coverage ability without running or excessive thickness
- Excellent finish
- Aerosol formulation gives quick, even spray
- CFC Free

3. TECHNICAL PROPERTIES:

PROPERTIES	SPECIFICATION
Appearance	White Colored liquid in Aerosol can
Specific Gravity	0.989 ± 0.08
% NVM	(30.00 ± 5.00)
Viscosity On Zahn Cup-1, at 28°C	34.00 ± 4 sec
Viscosity On Ford Cup-4 at 28 °C	15.00 ± 3 sec
Inside pressure (m.pa) @ 28 °C	0.40 ± 0.10
Flash Point	7.00 ± 3°C
Drying time (Surface dry)	5-10 Minutes
Drying time (Hard dry)	After 24 Hrs.
VOC Content	454 g/l
Finish	Smooth
Film Hardness/ Marking	Flexible & hard film.
Res. to washing & abrasion	Satisfactory
Res. To heat & humidity	Satisfactory up to 100°C with high humidity.
Hot water immersion test/ Sealing test	Passes & satisfactory

4. TYPICAL APPLICATIONS:

Shake vigorously till glass agitator rattle in the can. Hold the container approximately 30 cm away from the object to be painted. Keep the can motion from side to side so that the coating is deposited

evenly. Better to apply several thin coating at an interval of min 10minutes. Better to store can at room temperature.

5. SURFACE PREPARATION:

The surface to be painted must be free from grease, dirt, moisture and rust after that treat with IPA to attain excellent results.

6. DRY AND RECOAT TIME:

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 15 minutes, to handle in 1 hour, and can be recoated anytime.

7. STORAGE AND SHELF LIFE:

The shelf life of Tub & Tile Ceramic spray paint is 3 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

8. PACKING:

PRODUCT	VOLUME	PACKAGE
TUB & TILE CERAMIC SPRAY PAINT	400 ml	12 CANS/CTNS

This information is provided in good faith based upon data and sources believed to be reliable and correct. Conditions of use, outside the control of the Company, dictate that no responsibility can be assumed for the ultimate performance of this product