

Product Data Sheet



ASMACO SEMI PERMANENT LINE MARKER SPRAY PAINT



ASMACO
LINE MARKER
SPRAY PAINT

Product Description:

ASMACO SEMI PERMANENT LINE MARKER SPRAY PAINT is a high quality fast drying acrylic line marking paint with xylene free formula. It will give clean and sharp lines and fit for all applications. Excellent line marking for grass, concrete, wood, tarmac and composites, even you can spray it anywhere and will get good results. Due to its high solid percentage giving its brighter and more opaque finish.

Key Performance Properties:

- High covering Power
- Semi-permanent xylene free formula.
- Its high solids will always give more brighter and opaque finish.
- Adheres to most common surfaces.
- Apply by hand or applicator

Applications:

It is widely used in many industries for marking, surveying, road marking, car parking, tennis courts, golf courses, warehousing and many more. Suitable for

- Highlighting holes, machine positions, fixing positions.
- Marking cable positions prior to drilling/cutting.
- Turf marking and landscaping use.
- Excavation and mining.

Direction For Use:

- Paint designed for inverted use only.
- Shake the Can vigorously for 2-3 minutes after weights are heard to rattle.
- To apply by hand, remove cap, turn upside down and pull nozzle towards tin using two fingers.
- Nozzle must be cleared in any pause during use.
- To clear after use, turn can pointing nozzle up and away from user and activate for 1 or 2 seconds.

RESTRICTION:

- Do not use this product if rain is imminent.
- Do not expose to temperatures exceeding 500C
- Do not spray on naked flame or any incandescent materials.
- Keep out of reach of children.
- Do not pierce or burn even after use.
- It may burn above 50°C

Product Data Sheet



Typical Properties:

Appearance	Liquid
Odor	Solvent
Solid %age	40±5
Density	1.15 g/cm ³ @20°C
Drying Time Soft dry	305± minutes
Drying Time (Hard dry)	60 ± 5 minutes
Complete curing	24 hours
Flash Point	< 0°C (Closed Cup)
Inside pressure (m.pa) @ 28 °C	0.40 ± 0.10

Storage and Shelf Life:

The shelf life of ASMACO SEMI PERMANET LINE MARKER SPRAY PAINT is 2 years when stored under normal condition of temperature and pressure away from direct sunlight. Do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children. Store in cool, dry conditions, between 5 and 25°C.

Packaging:

ASMACO LINE MARKER SPRAY PAINT 750 ML - 12 CANS/CTN

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107
P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE